



## TVM Gun Foam

### Selecting the Correct foam:

**TVM Cold Weather** gun foam is formulated to expand and cure at temperatures of as low as 14°F (-10°C) to give an airtight, water resistant seal. PN 1-86-15-006

**TVM Door and Window** gun foam is formulated for low curing pressure and expansion; this foam may be confidently used in installations of door and window without fear of over expansion. PN 1-82-15-006

**TVM FireBlock** gun foam is a fireblock for wood-frame constructions. This method of fireblocking is used in place of mineral wool, fiberglass and caulks. PN 1-83-15-007

**TVM Gap Fill** gun foam is a low expansion polyurethane foam that expands to fill gaps, cracks and voids while sealing, insulating and deadening sound transmission. PN 1-81-15-006

## READ INSTRUCTIONS AND SAFETY RECOMMENDATIONS THOROUGHLY BEFORE USE.

Application Temperature: 41°F to 95°F (5°C to 35°C) / \*Cold Weather 14°F to 95°F (-10°C to 35°C)

- 1) Always wear work clothing, protective eyewear and gloves.
- 2) Ensure application surfaces are free from dust or other foreign materials.
- 3) To enhance product performance, moisten the application area using a spray bottle.
- 4) Shake the can vigorously for 15 seconds to ensure the propellant is evenly distributed.
- 5) With the can in its upright position, screw the dispenser onto the valve. Invert the can and slowly dispense product.
- 6) It is recommended that first time users become accustomed to the use of this foam by practicing on scrap cardboard or plastic.
- 7) Dispense foam into the area to be filled, pointing the gun into the far end of the cavity or void. Adjust the extrusion rate as required.
- 8) Fill the void approximately 50% to allow for expansion (fill 30% for Gap Fill & Mega Fill). (When working with larger voids, apply in 1" layers, misting each layer with water before applying subsequent layers.
- 9) Allow 24 hours for complete cure.
- 10) Unfinished cans may be reused within a short period of time when stored in the direction of use, attached to the dispenser.
- 11) To reuse, shake vigorously for 1 minute before dispensing.

\*Check local building codes for compliance before installation. This installation sheet is intended solely to provide an overview of the proper use of TVM gun foam products. This Installation sheet is not intended to make recommendations regarding the suitability of TVM gun foam products for a specific application, nor is it intended to illustrate proper construction methods – which are ultimately the responsibility of the builder or contractor.

**Limited Warranty:** TVM Building Products warrants only that its products will meet the specifications outlined on the technical data bulletin for each particular product. TVM Building Products will in no event be liable for damages resulting from any incident or consequences of that incident. TVM Building Products' warranty is limited to the stated selling price or replacement of product for any product found defective.

